App. No.: 10/585,487

Response to Final Office Action of November 16, 2011

Amendment with RCE dated February 13, 2012

Amendments to the Claims:

The following listing of the claims replaces all previous listings and versions of the

claims in this application:

<u>Listing of the claims</u>:

1. (Cancelled)

2. (Currently Amended) The building element according to claim [[1]] 31, said fibers being

glass fibers.

3. (Cancelled)

4. (Currently Amended) The building element according to claim [[1]] 31, wherein the difference

between the coefficient of thermal expansion of said pultruded elements and said specific

coefficient of thermal expansion is less than 40%.

5. (Currently Amended) The building element according to claim [[1]] 31, wherein the content

of fibers of said pultruded elements is more than 40% by weight.

6. (Currently Amended) The building element according to claim [[1]] 31, said first and second

pultruded elements being adhered to said self-supporting, load-bearing glass panel by means of

at least one of a PU adhesive and an epoxy adhesive.

Claims 7-8: (Cancelled)

9. (Currently Amended) The building element according to claim [[1]] 31, wherein said self-

supporting, load-bearing glass panel is a first self-supporting, load-bearing glass panel, said

building element further comprising a second self-supporting, load-bearing glass panel

positioned in a spaced apart relationship relative to said first self-supporting, load-bearing glass

panel by means of distance elements for providing a glazed window.

App. No.: 10/585,487

Response to Final Office Action of November 16, 2011

Amendment with RCE dated February 13, 2012

10. (Currently Amended) The building element according to claim 9, each of said distance

elements comprising extensions an extension of one of said pultruded elements.

11. (Previously Presented) The building element according to claim 10, said distance elements

further including a vapor absorbing substance.

12. (Currently Amended) The building element according to claim 10, further including a gas

tight foil between said first and second self-supporting, load-bearing glass panels.

13. (Original) The building element according to claim 12, said gas tight foil being integrally

included within said distance elements in an integral pultrusion or pultrusion/extrusion process.

Claims 14-15: (Cancelled)

16. (Currently Amended) The method according to claim [[15]] 32, said fibers being glass

fibers.

Claims 17-30: (Cancelled)

31. (New) A building element comprising:

a self-supporting, load-bearing glass panel defining an outer rim including first and

second opposed vertical segments of a predefined length, and first and second opposed

horizontal segments, said glass panel having a specific coefficient of thermal expansion; and

no more than first and second pultruded elements, each having a length equal to said

predefined length, adhered in a high strength integral adhesion to said glass panel along only said

first and second vertical segments, respectively, whereby none of said pultruded elements is

adhered to said glass panel along either of said first and second horizontal segments;

App. No.: 10/585,487

Response to Final Office Action of November 16, 2011

Amendment with RCE dated February 13, 2012

wherein said pultruded elements having a content of reinforcing fibers_that provides a

coefficient of thermal expansion of said pultruded elements approximately equal to said specific

coefficient of thermal expansion.

32. (New) A method of producing a building element comprising:

providing a self-supporting, load-bearing glass panel defining an outer rim including first

and second opposed vertical segments of a predefined length, and first and second opposed

horizontal segments, said glass panel having a specific coefficient of thermal expansion;

providing first and second pultruded elements, said pultruded elements, each having a

length equal to said predefined length and having a content of reinforcing fibers that provides a

coefficient of thermal expansion of said pultruded elements approximately equal to said specific

coefficient of thermal expansion; and

adhering said self-supporting, load-bearing glass panel to said first and second pultruded

elements in a high strength integral adhesion along only said first and second vertical segments,

respectively.

Docket No. 606-134.101